

KNIKMOPS SILOKAMM

- Aangedreven door Knikmops I20
- Grote wendbaarheid
- Stabiele knik-pendelbesturing.
- Probleemloos in lage en smalle staldoorgangen.
- Dosering via extra regeleenheden



deschans

De Schans BV

Drielseweg 46a | 5321 NC Hedel
073 5991750 | www.knikmops.com

KM120 SILOKAMM

Technische gegevens | Technical specifaction | Technische Daten



KM120		
[mm]	Totale lengte / Total length / Gesamtlänge	5000
[mm]	Totale breedte / Overall width / Gesamtbreite	2500
[mm]	Totale hoogte / Overall height / Gesamthöhe	2170/2260
[m3]	Inhoud / Capacity / Inhalt	3,8/4,6m3
[mm]	Zithoogte / Seat height / Sitzhöhe	1270
[L]	inhoud brandstoftank / Fuetank capacity / Inhalt Kraftstofftank	37
	Type dieselmotor / Diesel engine type / Art Dieselmotor (Kubota)	D1105
[kW/pk]	Motorvermogen / Engine power / Motorleistung	19/25
	Aantal cilinders / Number of cylinders / Zylinderzahl	3
	Aandrijfhydrauliek / Drive hydraulics / Antriebshydrauliek	plunjerpomp
	Wiel aandrijving / Wheeldrive / Radantrieb	plunjermotor
[L/min]	Debiet werkhydrauliek / Output of work hydraulics / Durchfluss Arbeitshydraulik	33
[bar]	Werkdruk hydrauliek / Pressure of work hydraulics / Betriebsdruck Arbeitshydraulik	180
[km/h]	Rijsnelheid / Topspeed / Geschwindigkeit	18

